



# INSTALLATION GUIDE

**2015+ FORD F-150 TOW HOOK LICENSE PLATE RELOCATION BRACKET**  
**SKU: MMLP-F150-15**

## TABLE OF CONTENTS

**Pg 1** RESOURCES & CONTACT INFORMATION

**Pg 2** IMPORTANT SAFETY INFORMATION

TOOLS NEEDED

SUPPLIED PARTS

BEFORE & AFTER

**Pg 5** INSTALLATION INSTRUCTIONS

**Pg 5** DISPOSAL INSTRUCTIONS  
WARRANTY INFORMATION

## RESOURCES & CONTACT



**CALL 1-877-GOMISHI**

CUSTOMER SERVICE HOURS: MON-FRI 8:30AM-5:00PM EST



**MISHIMOTO**



**GOMISHIMOTO**



**MISHIMOTO**



**WEBSITE**

[WWW.MISHIMOTO.COM](http://WWW.MISHIMOTO.COM)



**ENGINEERING BLOG**

[WWW.MISHIMOTO.COM/ENGINEERING](http://WWW.MISHIMOTO.COM/ENGINEERING)

## IMPORTANT SAFETY INFORMATION

- Mishimoto recommends you use safety glasses and protective gloves during the installation of our products
- Raise vehicle only on jack stands or on a vehicle lift
- Allow vehicle to cool completely prior to attempting installation
- Do not run the engine or drive the vehicle while overheating; serious damage can occur
- Please dispose of any liquids properly
- Mishimoto is not responsible for any vehicle damage or personal injury due to installation errors, misuse, or removal of Mishimoto products
- If you need any assistance while installing our products, reach out to our Customer Service Team at 1-877-GOMISHI

## TOOLS NEEDED

- (2) 10MM WRENCH
- 4MM ALLEN WRENCH

## SUPPLIED PARTS

- |                           |                          |
|---------------------------|--------------------------|
| (1) LICENSE PLATE BRACKET | (2) LOCK WASHERS         |
| (1) MOUNTING PLATE        | (2) M6 NUTS              |
| (2) M6 HEX HEAD BOLTS     | (4) M6 BUTTON HEAD BOLTS |
| (2) FLAT WASHERS          |                          |

## BEFORE



## AFTER



CONTINUED ON FOLLOWING PAGE

## INSTALLATION INSTRUCTIONS

- 01.** With the supplied M6 hex head bolts inserted through the slots in the license plate bracket, place the bracket on top of the tow hook with the bolts going through the hook.



- 02.** Insert the mounting plate into the bottom of the tow hook and, using (2) 10mm wrenches, secure it to the bolts with the supplied flat washers, lock washers, and nuts.



CONTINUED ON FOLLOWING PAGE

03. Using a 4mm Allen wrench, attach license plate to the bracket with the supplied M6 button head bolts.



**Congratulations! You have completed your installation.**

***\*For Disposal Instructions, and Warranty Information continue to the following page.***



## DISPOSAL INSTRUCTIONS

- › Do not dispose of any product as unsorted municipal waste. Use separate collection facilities. Contact your local authority for information regarding the collection systems available.
- › Never improperly dispose of any coolant, oil, or other chemicals.

## WARRANTY INFORMATION



- › All claims must be accompanied with a picture of the Mishimoto product showing the issue for which the claim is being submitted.
- › Mishimoto asks that the customer inspect their purchased item for any damage immediately upon arrival.
- › Any product deemed dead on arrival (DOA) must be claimed within 14 business days of delivery. Claims outside of this time frame will not be covered under the Mishimoto Lifetime Warranty.
- › This warranty does not include payment and/or reimbursement of the cost of labor in connection with the removal of any product returned pursuant to the warranty policy or in connection with the installation of any replacement items provided under the warranty policy.
- › Mishimoto has the right to refuse a claim at any time.

- › When Mishimoto accepts a claim, Mishimoto retains full discretion to choose if it will: (i) repair or replace purchaser's original Mishimoto product; (ii) replace purchaser's original Mishimoto product with the most current available model; or (iii) provide the purchaser with a gift card redeemable on [Mishimoto.com](https://www.mishimoto.com) in the amount of the original purchase price of the original Mishimoto product. The provision of a replacement of a Mishimoto product is subject to availability and Mishimoto retains the right to substitute any warranty claim item with a comparable item or credit at any time.
- › If Mishimoto determines that it will provide a replacement item in connection with a claim under this warranty policy, and such item is out of stock, Mishimoto will place the customer on backorder and ship the replacement product to the purchaser once it becomes available.
- › Mishimoto is not liable for incorrect shipments in connection with a claim if a claim form is completed incorrectly, or if a model number is not included in a claim.
- › If you have a vehicle equipped with an automatic transmission, please make sure to specify this within the text box on the claim form. Mishimoto is not responsible for incorrect replacement shipments if transmission type is not indicated.



**WARNING**  
Cancer and  
Reproductive Harm  
[www.P65Warnings.ca.gov](https://www.P65Warnings.ca.gov)

This product can expose you to chemicals which are known to the state of California to cause cancer. For more information visit: [www.p65warnings.ca.gov](https://www.p65warnings.ca.gov)